

产品简介

Introduction

ADS 右进料压接模具，完美匹配市面上主流的欧式半自动和全自动压线机。ADS 压接模具采用模块化设计，模具备件能够与海昌常规模具相互替换，减少易损件备货。

ADS applicator perfectly match with the mainstream European semi-automatic and fully automatic crimping machine on the market. ADS applicator adopts modular design, spare parts can be replaced with those on Hacint conventional applicator, which reduces the vulnerable parts in stock.

产品特征

Feature

●调节系统

盘式和楔块式两种结构可以自由切换, C.H./H.调整精度 0.02mm, 调节范围 2mm;
调节节奏感强，刻度易识别

Adjustment

Freely switch between disk dial and wedge dial. The adjustment accuracy of C.H./H. is 0.02mm and the adjustment range is up to 2mm. Strong sense of rhythm and legible scale.

●托料结构

定制化设计，送料稳定

Feeding mechanism

The holder is designed according to the shape of the terminal, which provide a stable feed.

●快换结构

完美匹配 komax、Hacint 等品牌半自动和全自动压线机

Quick change: Perfectly fit with Komax, Hacint press and fully automatic crimping applicator machine.

●技术文件

提供完整的使用、保养说明书，若有要求也可以提供机器能力研究、断面分析报告等文件

Technical documentation

You can get a complete technical documentation containing all the information needed to safely use and correctly maintain the equipment.

Upon request, a capability study & cross-section analysis can be provided.

●超强抗锈

QW 表面处理

Strong resistance to rust

QW surface plating.

●产品追溯

每个零件都拥有自己的 ID

Production tracking

Laser labeling for each part-unique ID.

●云端数据

扫描二维码，实时查看出厂资料信息

Cloud data

Scan QR code on each name plate to get the data of the applicator in real time.

产品参数

Specifications

型号 Type	ADS	端子料厚 Terminal thickness	1.2mm（MAX）
行程 Stroke	40mm	送料机构 Feed mechanism	气动 Pneumatic
料带形式 Strip form	右侧进料 Right side feed	送料步距 Feeding step	40mm
闭合高度 Shut height	135.78mm 5.346in	重量 Weight	5Kg
适应线径 Wire size	0.08-6.0mm ²	尺寸 Dimensions(mm)	L200*W150*H170