

HBQ-375 双工位热缩机

产品简介

HBQ-375 是一种将热缩管收缩到线束上的设备，适用于大线的端部或中间位置热缩。如中间波纹管热缩管热缩，较粗的电瓶线，较大的搭铁端子线。双工位持续作业，保护非热缩区线束和护套。

产品特征

●高效

不同样式：护套线/搭铁线；

多工位：双工位可保证连续作业；

●安全

可调工装，可定制，可保护非加热区的安全；

●支持扩展

支持 MES 联网；

产品参数

型号	HBQ-375
线径范围	0~120mm ²

热缩管长度	300mm（max）
加热板温度	600℃（max）
电源	AC220V/18.5A
功率	3KW（max）
尺寸	L1400×W970×H1730mm
重量	200kg
选配件	摄像头 工控机电脑屏

HBQ-375 Dual-station Heat Shrink Machine

INTRODUCTION

HBQ-375 is a machine that shrinks heat-shrink tubing onto wire harnesses, suitable for heat-shrinking the ends or middle sections of large wires. It is suitable for heat-shrinking intermediate corrugated tubing, thicker battery wires, and larger ground terminal wires. The dual-station operates continuously to protect the wire harness and housings in the non-heat-shrinkable areas.

FEATURES

● Efficient

Different styles: housing wire/bonding wire.

Multi-station: Dual-station ensures continuous operation.

● security

Adjustable fixtures, customizable, and capable of protecting the safety of non-heating areas.

● Support for extension

support MES networking.

SPECIFICATIONS

Type	HBQ-375
Wire Cross Section	0~120mm ²
Heat Shrink Tube Length	300mm(max)
Heating Board Temperayure	600°C
Power	3KW(max)
Power Supply	AC220V/18.5A
Overall Dimension	L1400×W970×H1730mm

Weight	200kg
Optional	Camera Industrial computer screen