

HBQ-362 四头点缠绞线机

产品简介

HBQ-362 四头点缠绞线机主要应用于线束加工领域，在绞线完成后可进行端部点缠，起到防松效果。

产品特征

● 高效

可前后旋转,提高工作效率;
绞合后自动点缠胶带;
自动感应夹线免除人工操作按钮的步骤;

● 智能

不同组数的拉力自动调节;
不同线径的拉力自动调节;
胶带点缠功能可选择开启关闭;

● 准确

四组线束独立自动拉直,装夹误差可消除;
在绞合过程中保证扭矩恒定,实现节距稳定;
胶带点缠位置稳定可靠;

产品参数

型号	HBQ-362
绞线范围	0.13~1mm ²
绞线长度	300~2000mm（可定制）
绞线速度	4000r/min（最大）
绞线根数	2/3 根
节距精度	±10%
胶带规格	宽 9mm 外径 80mm 内径 38mm（可定制）
胶带材质	PVC
胶带长度	30mm±3mm（不可调）
开口长度	30-100mm
气源	5~6Bar
电源	AC220V
尺寸	L3400×W1100×H1600mm
重量	410kg

HBQ-362 Four-Wire Twisting Machine

INTRODUCTION

HBQ-362 Four-wire twisting machine, mainly utilized in the field of wire harness processing, could make tape point wrapping serving as an anti-loosening function after twisting finalized.

FEATURES

- Efficiency

It can rotate forward and backward, improving work efficiency;

Automatically apply adhesive tape after twisting;

The automatic sensing thread clamping eliminates the need for manual operation of buttons;

- Intelligence

Automatic adjustment of tension for different sets;

Automatic adjustment of tension for different wire diameters;

Tape point wrapping function could be optional(on or off);

- Accuracy

Four sets of wire harnesses are independently and automatically straightened, eliminating clamping errors;

Ensure a constant torque during the stranding process to achieve stable pitch;

The position of the tape's point wrapping is stable and reliable.

SPECIFICATIONS

Type	HBQ-362
Wire Size	0.13-1mm ²
Twisting Length	300-2000mm(customized)
Twisting Speed	4000r/min(max)
Twisting Piece	2/3pcs
Pitch Accuracy	± 10%
Tape Material	PVC
Tape Specification	Width:9mm OD:80mm ID:38mm(customized)
Tape Length	30± 3mm(fixed)
Open Length	30-100mm
Air Supply	5-6Bar
Power Supply	AC220V
Dimension	L3400× W1100× H1600mm

Weight	410kg
--------	-------